

EPSON® EU-T400 Series Thermal Kiosk Printer



STANDARD FEATURES

- Modular design for easy mounting/integration
- Drop in paper loader
- Serial and parallel interfaces
- Graphics printing
- Fast printing up to 6 ips
- All steel chassis

APPROVALS



SPECIFICATIONS

Paper Width:

80 mm standard

Paper Thickness:

60-120 um with loop
183 um with no loop

Paper Diameter:

8 in outer max

Interface:

RS-232 to 38 lb

D8-9 Connection

Parallel

Autocutter:

Full-cut, guillotine style

Dimensions:

6 in: 7.7 x 6.7 x 11.8 in (195.6 x 170.2 x 152.4 mm)
8 in: 7.7 x 6.7 x 13.8 in (195.6 x 170.2 x 350.5 mm)

Weight:

3.9 kg (8.6 lb)

Print Method:

Direct thermal single & two-color printing
(with special paper)

Print Speed:

150 mm/sec

Print Width:

72-104 mm (adjustable)

Presenter Option:

Bidirectional, friction feed loop

Power Required:

24 vdc

Environmental:

10-80% operating temperature and humidity

Sensors:

Paper end, black mark
Photo sensor/ Platen open, cutter blade position
Micro switch/Print head temperature

Approvals:

UL listed, CSA

Warranty:

One-year limited warranty

PART NUMBER/PRICE

PART #	DESCRIPTION	WEIGHT	PRICE
105443	EU-T400/T432, embedded unit for kiosk vertical, RS-232 and parallel (requires power supply)	13 lb	Consult
23112	Power supply, PS-180		Consult

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
105445	Paper 80 mm wide, 6 in O.D., 1 in core, 690 ft/roll, wound out	Consult
105446	Paper 80 mm wide, 8 in O.D., 1 in core, 1268 ft/roll, wound out	Consult
66535	Cable, 9-Pin female to 9-Pin female, null modem to PC, 6 ft	Consult