



# EPSON® EU-T482 Series Thermal Kiosk Printer



## STANDARD FEATURES

- Modular design for easy mounting/integration
- Drop in paper loader
- RS-232 and USB interfaces
- Graphics printing
- Fast printing up to 6 inches per second
- All steel chassis

## APPROVALS



## SPECIFICATIONS

**Paper Width:**

79 mm standard ±5

**Paper Thickness:**

60-150 um

**Paper Diameter:**

6 in (152.4 mm) outer max  
8 in (203 mm) outer max

**Interface:**

USB complies with USB 2.0  
RS-232 male D-Sub 9-Pin connector

**Autocutter:**

Full-cut

**Dimensions:**

7.64 x 6.7 x 14.72 in (194 x 170 x 374 mm)

**Weight:**

10 lb (4.5 kg)

**Print Method:**

Direct thermal single sheet

**Print Speed:**

6.0 in (153 mm) per sec

**Print Width:**

2.84 in (72 mm) adjustable

**Presenter Option:**

Friction feed

**Power Required:**

24VDC (PS-180 power supply)

**Environmental:**

Temperature 41°F to 122°F (5°C to 50°C)  
Humidity 10 to 80% RH

**Sensors:**

Paper near end sensor  
Auto cutter reset sensor  
Print head temperature sensor  
Platen open sensor  
Black mark sensor

**Approvals:**

UL listed, CSA

**Warranty:**

One-year limited warranty

## PART NUMBER/PRICE

PART #	DESCRIPTION	WEIGHT	PRICE
155751	EU-T482-011, embedded unit for kiosk vertical, (requires power supply)	13 lb	Consult
23112	Power supply, PS-180		Consult

## OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
105445	Paper 80 mm wide, 6 in O.D., 1 in core, 690 ft/roll, wound out	Consult
105446	Paper 80 mm wide, 8 in O.D., 1 in core, 1268 ft/roll, wound out	Consult
66535	Cable, 9-Pin female to 9-Pin female, null modem to PC, 6 ft	Consult
22436	Cable, comm 9-Pin D-subF to blunt end	Consult

